

Hebei Yezhen Wire Mesh Products Co.,Ltd Address:Anping county,Hebei Province,China E-mail:alan@wiremeshyz.com Tel:+86 18132114364

<u>358 Fence</u>

YeZhen supplies both posts and 358 mesh panels in a galvanised and polyester powder-coated finish in any of a wide range of standard RAL colors, with non-standard colour available to order.

Compared with high-security palisade, high-security mesh panel fencing is similarly difficult to scale, harder to cut and makes it impossible to pass through all but very small objects. Mesh panel fencing can also be considerably higher (6 m rather than 4 m for palisade).

The Characteristic of Hot-dip Galvanized 358 Fence Netting:

Good corrosion resistance, anti-aging, easy and quick installation, anti-climbing, anti-cut, beautiful appearance, Smooth surface, excellent visibility, Low maintenance costs.

1. Type

142041- Hot-dip Galvanized 142042- Galvanizing + Powder coated

- 2. Specification
- a. Standard mesh panel- 2D

Image	Mesh size	Height (mm)	Width (mm)	Wire diameter	Post Height	No. Of brackets
	76.2x12.7mm 75x12.5mm 75x13mm	2100	2515/2750/3000		2700	7
		2200	2515/2750/3000	2.0-4.0mm	2800	8
		2400	2515/2750/3000		3000	9
		2700	2200/2300		3700	10
		3000	2200/2300		4000	11
		3600	2200/2300		4800	12
		4000	2200/2300		5200	14

b. Standard Mesh Panels-3D

Image	Mesh size	Height (mm)	Width(mm)	Wire diameter	No. Of curves	Post Height	No. Of brackets
	76.2x12.7mm	1800	2515/2900/3000		3	2600	6
	75x12.5mm	2000	2515/2900/3000	3.0-4.0mm	4	2700	7
	75x13mm	2200	2515/2900/3000		4	2800	8



Hebei Yezhen Wire Mesh Products Co.,Ltd Address:Anping county,Hebei Province,China E-mail:alan@wiremeshyz.com Tel:+86 18132114364

2400	2515/2900/3000	4	3000	9
2700	2515/2900/3000	5	3500	10
3000	2250/2500	5	4000	12
4000	2250	5	5200	14

Fence Post

	P1-SHS	P2-IPE	P3-RHS	P4-C+F	
	Square post	IPE post	Rectangle post	C post with flat bar	
Popular size A	60x60	100x55	60x80	60x80	
Popular size B	80x80	100x68	80x100	80x100	
Popular size C	100x100	120x74	100x150	100x150	
Thickness	1.2-1.5mm	1.2-2.0mm	2.5-5.0mm	2.0-5.0	